

14126 GANNET ST. SUITE 107 SANTA FE SPRINGS, CA 90670 FON: 562.483.1445 • FX: 562.483.1446 WWW.MDCTINC.COM



INSTALLATION INSTRUCTIONS:

- 1) CONNECT THE RED WIRE TO THE 12 VOLT LINE OF YOUR CAR RADIO OR STEREO. (THIS IS THE RED WIRE CONNECTED TO THE FUSE)
- 2) CONNECT THE BLACK WIRE TO THE METAL OF THE DASHBOARD IN A SECURE MANNER TO GROUND PROPERLY. (THIS IS THE LONGEST BLACK WIRE)

SPEAKER WIRES:

- 1) YOU MAY CONNECT THE RED WIRE TO THE LEFT SPEAKER WIRE OF THE CAR RADIO AND THE YELLOW WIRE TO THE RIGHT SPEAKER OF YOUR CAR RADIO. THIS WILL ENABLE YOU TO RECEIVE LIGHT FROM BOTH CHANNELS OF YOUR CAR RADIO.
- *DO NOT CONNECT THE OTHER BLACK (THE SHORTER) WIRE TO ANYTHING, CONNECTING THIS BLACK WIRE WILL CAUSE THE PRODUCT TO SHORT CIRCUIT. THERE IS NO NEED TO ADD AN ADDITIONAL GROUND, THIS SYSTEM OPERATES ON A NEUTRAL GROUND.

MOUNTING UNIT:

THERE ARE TWO SCREWS INCLUDED TO MOUNT THE UNIT TO THE BOTTOM OF YOUR DASHBOARD. THE MOUNTING BRACKETS HAVE ADJUSTABLE SLOTTED SCREW HOLES TO MOVE FORWARD OR BACKWARD. DO NOT MOUNT ON THE TOP OF YOUR DASHBOARD IT MAY CAUSE A DISTRACTION WHILE DRIVING.

IT IS HIGHLY RECOMMENDED THAT YOU SELECT YOUR SENSITIVITY BEFORE OPERATING YOUR VEHICLE AND ONLY MAKE ADJUSTMENTS WHILE YOUR VEHICLE IS PARKED AND NOT IN MOTION.



DO NOT MOUNT THE UNIT ANYWHERE THAT MAY OBSTRUCT YOUR VIEW WHILE DRIVING YOUR VEHICLE. ALWAYS SELECT YOUR SENSITIVITY BEFORE OR AFTER OPERATING YOUR VEHICLE.

